



Vertical Air Laminar Flow Cabinet TRVLC-603

www.safetyzon.com | info@safetyzon.com

Description

Vertical Air Laminar Flow Cabinet TRVLC-603 is equipped with a wind volume adjustable fan system, with an average wind speed of 0.25 to 0.45 m/s. It has a single - single dimension. It has a HEPA filter as well as a primary filter. With a stainless steel work area and a glass sliding door. Consumption of maximum power of 400 W. A digital display panel with a crystal liquid interface controls the system. It comes with a power outlet.

Features:

- > The vertical closed worktop effectively prevents outside gas from entering and the weird odor
- > It employs a wind volume adjustable fan system
- > A light-touch type switch and a dual-speed voltage regulation device to maintain a suitable wind speed in the working area
- > The personalized design takes into account all of the user's requirements
- > It uses a spring-type sliding door that can be oriented in the desired position
- > It is designed to be operated easily
- > The front cover can be easily accessible to swap screens and electrical equipment
- > The work area made with a stainless steel
- > Having a digital display operates with a liquid crystal interface

Specifications :

Dimension Of Working Area(W1×D1×H1)	880×650×580mm
Half Ventilation Peak Value	? 3?m(XYZ direction)
Illumination	?300LX
Maximum Power Consumption	400W
Noise	?62dB
Number Of Bacteria	?0.5per utensil. Hour (90mm utensil)
Overall Dimension (W×D×H)	1040×690×1600mm
Power Supply	AC, 220 V/50Hz
Specification And Number Of A Fluorescent Lamp Or UV Lamps Of Ultraviolet Lights	8W×1/10 W×1
Suited Number	single-single
The Average Wind Speed	0.25 to 0.45m/s



West 110th Street Overland Park KS 66210, USA
Email: info@safetyzon.com | Website: www.safetyzon.com